



# Safety Data Sheet

Issue Date: 06-Nov-2017

Revision Date: 06-Nov-2017

Version 1

## 1. IDENTIFICATION

### Product Identifier

**Product Name** F-Seal White

### Other means of identification

**SDS #** RD-0181

### Recommended use of the chemical and restrictions on use

**Recommended Use** Seal HVAC Duct Systems.

### Details of the supplier of the safety data sheet

#### **Supplier Address**

Red Devil, Inc.  
4175 Webb Street  
Pryor, Oklahoma 74361  
www.reddevil.com

### Emergency Telephone Number

**Company Phone Number** 918-825-5744  
Fax: 918-825-5761  
**Emergency Telephone (24 hr)** INFOTRAC 1-352-323-3500 (International)  
1-800-535-5053 (North America)

## 2. HAZARDS IDENTIFICATION

**Appearance** White liquid

**Physical state** Liquid

### Classification

Skin sensitization	Category 1
Carcinogenicity	Category 2

### Signal Word

Warning

### Hazard statements

May cause an allergic skin reaction  
Suspected of causing cancer



**Precautionary Statements - Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Contaminated work clothing must not be allowed out of the workplace  
 Wear protective gloves

**Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention  
 IF ON SKIN: Wash with plenty of water and soap  
 If skin irritation or rash occurs: Get medical advice/attention  
 Wash contaminated clothing before reuse

**Precautionary Statements - Storage**

Store locked up

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Other hazards**

Harmful to aquatic life with long lasting effects

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Please also refer to subsequent sections of this SDS for additional information regarding the components of this product.

Chemical Name	CAS No.	Weight-%
Calcium Carbonate	1317-65-3	40-50
Ethyl acrylate	140-88-5	5-10
Titanium dioxide	13463-67-7	0.1-0.5
Quartz	14808-60-7	0.1-0.5
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	0.1-0.5

\*\*If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.\*\*

### 4. FIRST AID MEASURES

**First Aid Measures**

<b>General Advice</b>	Provide this SDS to medical personnel for treatment.
<b>Eye Contact</b>	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Skin Contact</b>	Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
<b>Inhalation</b>	Remove exposed individual(s) to fresh air for 20 minutes. Consult a physician/poison center if individual's condition declines or if symptoms persist.
<b>Ingestion</b>	Rinse mouth. Do not induce vomiting without medical advice. Get medical advice/attention.

**Most important symptoms and effects**

**Symptoms** Exposed individuals may experience eye tearing, redness and discomfort. Overexposure to vapors during application and curing may mildly irritate respiratory tract and result in coughing and sneezing.

**Indication of any immediate medical attention and special treatment needed**

**Notes to Physician** Provide general supportive measures and treat symptomatically.

**5. FIRE-FIGHTING MEASURES****Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable Extinguishing Media** Not determined.

**Specific Hazards Arising from the Chemical**

Product is not flammable.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

**Personal Precautions** Wear protective clothing as described in Section 8 of this safety data sheet.

**For Emergency Responders** Restrict access to spill area.

**Environmental precautions**

**Environmental precautions** Minimize use of water to prevent environmental contamination. Prevent spill or rinse from contaminating storm drains, sewers, soil or groundwater. See Section 12 for additional Ecological Information.

**Methods and material for containment and cleaning up**

**Methods for Containment** Prevent further leakage or spillage if safe to do so. Use absorbent material to contain spill.

**Methods for Clean-Up** Sweep up absorbed material and shovel into suitable containers for disposal. Wash area with soap and water. For waste disposal, see section 13 of the SDS.

**7. HANDLING AND STORAGE****Precautions for safe handling**

**Advice on Safe Handling** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves. Keep out of the reach of children. Use with adequate ventilation.

**Conditions for safe storage, including any incompatibilities**

<b>Storage Conditions</b>	Keep container tightly closed and store in a cool, dry and well-ventilated place. Store locked up.
<b>Incompatible Materials</b>	Strong oxidizing agents.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Calcium Carbonate 1317-65-3	-	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Ethyl acrylate 140-88-5	STEL: 15 ppm TWA: 5 ppm	TWA: 25 ppm TWA: 100 mg/m <sup>3</sup> (vacated) TWA: 5 ppm (vacated) TWA: 20 mg/m <sup>3</sup> (vacated) STEL: 25 ppm (vacated) STEL: 100 mg/m <sup>3</sup> (vacated) S* S*	IDLH: 300 ppm
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>
Quartz 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable particulate matter	TWA: 50 µg/m <sup>3</sup> TWA: 50 µg/m <sup>3</sup> excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m <sup>3</sup> respirable dust : (250)/( %SiO <sub>2</sub> + 5) mppcf TWA respirable fraction : (10)/( %SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA respirable fraction	IDLH: 50 mg/m <sup>3</sup> respirable dust TWA: 0.05 mg/m <sup>3</sup> respirable dust

**Appropriate engineering controls**

<b>Engineering Controls</b>	Apply technical measures to comply with the occupational exposure limits. Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the SDS. Ensure that eyewash stations and safety showers are close to the workstation location.
-----------------------------	---

**Individual protection measures, such as personal protective equipment**

<b>Eye/Face Protection</b>	Use approved safety goggles or safety glasses. If necessary, refer to appropriate regulations and standards. Refer to 29 CFR 1910.133 for eye and face protection regulations.
<b>Skin and Body Protection</b>	<p>Skin: Wear chemical impervious gloves (eg: Nitrile or Neoprene). Use triple gloves for spill response. If necessary, refer to appropriate regulations &amp; standards.</p> <p>Body: Use protection appropriate for task (eg: lab coat, coveralls, Tyvek suit). If necessary, refer to OSHA Technical Manual (Sec. VII: Personal Protective Equipment). Use foot protection, as described in appropriate regulations &amp; standards.</p>
<b>Respiratory Protection</b>	If mists or sprays are created, use appropriate respiratory protection. Oxygen levels below

19.5% considered IDLH by OSHA. In such instances, use full-facepiece pressure demand SCBA or a full facepiece, supplied air respirator w/ auxillary self-contained air supply.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	Liquid	<b>Odor</b>	Not determined
<b>Appearance</b>	White liquid	<b>Odor Threshold</b>	Not determined
<b>Color</b>	White		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
<b>pH</b>	Not determined	
<b>Melting Point/Freezing Point</b>	Not determined	
<b>Boiling Point/Boiling Range</b>	Not determined	
<b>Flash Point</b>	Not determined	
<b>Evaporation Rate</b>	Not determined	
<b>Flammability (Solid, Gas)</b>	Not determined	
<b>Flammability Limits in Air</b>		
<b>Upper Flammability Limits</b>	Not determined	
<b>Lower Flammability Limit</b>	Not determined	
<b>Vapor Pressure</b>	Not determined	
<b>Vapor Density</b>	Not determined	
<b>Relative Density</b>	Not determined	
<b>Water Solubility</b>	Not determined	
<b>Solubility in other solvents</b>	Not determined	
<b>Partition Coefficient</b>	Not determined	
<b>Auto-ignition Temperature</b>	Not determined	
<b>Decomposition Temperature</b>	Not determined	
<b>Kinematic Viscosity</b>	Not determined	
<b>Dynamic Viscosity</b>	Not determined	
<b>Explosive Properties</b>	Not determined	
<b>Oxidizing Properties</b>	Not determined	

## 10. STABILITY AND REACTIVITY

### Reactivity

Not reactive under normal conditions.

### Chemical Stability

Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

Silica will dissolve in hydrofluoric acid producing a corrosive gas, silicon tetrafluoride.

**Hazardous Polymerization**      Hazardous polymerization does not occur.

### Conditions to Avoid

Incompatible Materials. Excessive heat or cold.

### Incompatible Materials

Strong oxidizing agents.

### Hazardous Decomposition Products

None known based on information supplied.

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure****Product Information**

<b>Eye Contact</b>	Eye contact may result in tearing, redness & pain.
<b>Skin Contact</b>	May cause an allergic skin reaction. Causes mild skin irritation. Prolonged and frequent contact may cause redness and irritation. Repeated skin contact may cause dermatitis.
<b>Inhalation</b>	Overexposure to vapors during application & curing may mildly irritate respiratory tract & result in coughing & sneezing.
<b>Ingestion</b>	May cause gastrointestinal irritation, nausea, diarrhea, and vomiting.

**Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Ethyl acrylate 140-88-5	= 550 mg/kg ( Rat )	= 500 µL/kg ( Rabbit ) = 1790 mg/kg ( Rabbit )	= 1410 ppm ( Rat ) 4 h = 1414 ppm ( Rat ) 4 h
1,2 Propanediol 57-55-6	= 20 g/kg ( Rat )	= 20800 mg/kg ( Rabbit )	-
Titanium dioxide 13463-67-7	> 10000 mg/kg ( Rat )	-	-
Petroleum distillates, solvent dewaxed heavy paraffinic 64742-65-0	> 15000 mg/kg ( Rat )	> 5000 mg/kg ( Rabbit )	> 2400 mg/m <sup>3</sup> ( Rat ) 4 h

**Information on physical, chemical and toxicological effects**

<b>Symptoms</b>	Please see section 4 of this SDS for symptoms.
-----------------	--

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

<b>Sensitization</b>	May cause an allergic skin reaction.
<b>Carcinogenicity</b>	Suspected of causing cancer. Silica (quartz) is a possible carcinogen when it appears as a respirable dust. Titanium dioxide is a possible carcinogen when it appears as a respirable dust. The component below belongs to the petroleum family, which has been shown to contain carcinogenic substances depending on the level of refinement. The carcinogen classification need not apply when the substance contains less than 3% dimethyl sulfoxide extract, as is the case with this product.

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethyl acrylate 140-88-5		Group 2B		X
Titanium dioxide 13463-67-7		Group 2B		X
Quartz 14808-60-7	A2	Group 1	Known	X
Petroleum distillates, solvent dewaxed heavy paraffinic 64742-65-0	A2	Group 1	Known	X

**Legend**

**ACGIH (American Conference of Governmental Industrial Hygienists)**

A2 - Suspected Human Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

**NTP (National Toxicology Program)**

Known - Known Carcinogen

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

**Target organ effects** Acute: Eyes & Skin. Chronic: Skin.

### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

**ATEmix (oral)** 5,469.00 mg/kg  
**ATEmix (dermal)** 10,869.00 mg/kg

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Harmful to aquatic life with long lasting effects.

### Component Information

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Ethyl acrylate 140-88-5	48: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50	10.0 - 22.0: 96 h <i>Leuciscus idus</i> mg/L LC50 static 2.31 - 2.7: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 4.6: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50	7.9: 48 h <i>Daphnia magna</i> mg/L EC50
1,2 Propanediol 57-55-6	19000: 96 h <i>Pseudokirchneriella</i> <i>subcapitata</i> mg/L EC50	51400: 96 h <i>Pimephales promelas</i> mg/L LC50 static 41 - 47: 96 h <i>Oncorhynchus mykiss</i> mL/L LC50 static 51600: 96 h <i>Oncorhynchus</i> <i>mykiss</i> mg/L LC50 static 710: 96 h <i>Pimephales promelas</i> mg/L LC50	1000: 48 h <i>Daphnia magna</i> mg/L EC50 Static 10000: 24 h <i>Daphnia</i> <i>magna</i> mg/L EC50
Petroleum distillates, solvent dewaxed heavy paraffinic 64742-65-0		5000: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50	1000: 48 h <i>Daphnia magna</i> mg/L EC50

### Persistence/Degradability

Not determined.

### Bioaccumulation

Not determined.

### Mobility

Chemical Name	Partition Coefficient
Ethyl acrylate 140-88-5	1.18

### Other Adverse Effects

Environmental Exposure Controls: Should be maintained so as to prevent release to the environment (atmospheric release, release to waterways & spills)

## 13. DISPOSAL CONSIDERATIONS

### Waste Treatment Methods

**Disposal of Wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated Packaging** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**US EPA Waste Number**

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Ethyl acrylate 140-88-5				U113

**14. TRANSPORT INFORMATION**

**Note** Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

**DOT** Not regulated

**IATA** Not regulated

**IMDG** Not regulated

**15. REGULATORY INFORMATION****International Inventories**

Chemical Name	TSCA	DSL/NDSL	EINECS/E LINCS	ENCS	IECSC	KECL	PICCS	AICS
Calcium Carbonate	X	X	X	Present	X	Present	X	X
Ethyl acrylate	X	X	X	Present	X	Present	X	X
1,2 Propanediol	X	X	X	Present	X	Present	X	X
Titanium dioxide	X	X	X	Present	X	Present	X	X
Quartz	X	X	X	Present	X	Present	X	X
Petroleum distillates, solvent dewaxed heavy paraffinic	X	X	X		X	Present	X	X

**Legend:**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations****CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Ethyl acrylate 140-88-5	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

**SARA 311/312 Hazard Categories**

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	Yes
<b>Fire Hazard</b>	No



<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Ethyl acrylate - 140-88-5	140-88-5	5-10	0.1

**CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**US State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Ethyl acrylate - 140-88-5	Carcinogen
Titanium dioxide - 13463-67-7	Carcinogen
Quartz - 14808-60-7	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Calcium Carbonate 1317-65-3	X	X	X
Ethyl acrylate 140-88-5	X	X	X
1,2 Propanediol 57-55-6	X		X
Titanium dioxide 13463-67-7	X	X	X
Quartz 14808-60-7	X	X	X

**16. OTHER INFORMATION****NFPA****Health Hazards****Flammability****Instability****Special Hazards****HMIS**

Not determined

Not determined

Not determined

Not determined

**Health Hazards****Flammability****Physical hazards****Personal Protection**

Not determined

Not determined

Not determined

Not determined

**Issue Date:**

06-Nov-2017

**Revision Date:**

06-Nov-2017

**Revision Note:**

New formula

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**