# MaxLite

PROJECT NAME:

NOTES:



CAT. #:

FIXTURE SCHEDULE:

## Enhanced Canopy/Parking Garage Fixture



### **Product Description**

Quick to install and pay for itself, the Enhanced Canopy/Parking Garage fixture is an economical retrofit solution for 70-250W HID garage and canopy luminaires. Offered in five wattages, both CCT and wattage selectable, with a single lens that meets both parking garage and canopy distributions, the CPL can address a variety of canopy lighting needs. The series comes standard with an internal c-Max control receptacle which allows for a variety of c-Max controls to be field installed (sold separately). The luminaire also features a single screw design that allows access to the fixture interior within seconds for guick and easy surface conduit connections or c-Max controls installation. In addition factory installed battery backup, 480V and White finish options are available. For Canopy/ Parking Garage applications, this family makes it easy!

#### Features

- Integrated/Embedded c-Max controls capability or factory installed Avi-On option
- Quick and easy access to interior with single screw and hinge design for conduit connection and controls installation
- CCT selectable between 3000/4000/5000K
- Wattage selectable on 60W version
- Universal 120-277V standard, High Voltage 277-480V option
- 4kV + 10kA surge protection standard, option for higher 20kA protection
- TAA compliance available contact Maxlite for details

#### Warranty

10 year standard

#### **Model Selection**

FAMILY	WATTAGE	VOLTAGE	-	сст	FINISH	CONTROL OPTIONS	EM OPTIONS	SURGE OPTIONS
CPL = Enhanced Canopy/Parking Garage	<b>20 =</b> 20W <b>30 =</b> 30W <b>40 =</b> 40W <b>52 =</b> 52W <b>60 =</b> 60W	U = 120-277V H* = 277-480V		CS = 3/4/5K WCS** = 3/4/5K, Wattage Selectable	B = Dark Bronze S = Silver L = Black W = White	CR = Controls Ready, c-Max compatible (standard)   CN = Control Node Installed   PN = PC Node Installed   NN = Network Node Installed   EA = External Adapter Installed   Installed AV = Low-Voltage Avi-on Installed	Blank = No Battery EM2= Battery Backup - 20C	Blank = 4kV + 10kA (standard) S = 20kA Surge Protector
					Contact Maxlite for additional finishes	Factory Installed	Factory Installed	Factory Installed

\* 40W, 52W and 60W only \*\* 60W Wattage Selectable (38/48/58W), 120-277V only