

Sensi Lite smart thermostat

The Sensi™ Lite smart thermostat puts energy savings in easy reach. Installation is quick and simple — no common wire required with most systems. The controls are familiar and intuitive. And, best of all, your usage activity and personal data stays private.



ST25U

SMART HAS NEVER BEEN SO EASY

Sensi Lite is everything you are looking for in a smart thermostat - energy savings, modern design with a sleek glass touchscreen and lasting quality you can trust in your home.

EASY INSTALLATION

Just open the app, follow a few easy steps and installation is a snap. And, unlike other smart thermostats, you won't need to worry about a c-wire in most systems.¹

ENERGY SAVINGS

Save about 23% on HVAC energy² through features like flexible scheduling, remote access and geofencing.

MONITOR HVAC PERFORMANCE

You can keep track of your HVAC system's performance with Smart Alerts, service reminders, usage reports and more.

DEMAND RESPONSE COMPATIBLE

Sensi's flexible API allows you to easily integrate into your demand response program. Offering more control and no additional charge for program data.

CONTROL FROM ANYWHERE

The top-rated Sensi mobile app for iOS and Android gives you total on-the-go access to adjust your thermostat from anywhere, anytime.

SMART HOME COMPATIBLE

Sensi Lite works well with Amazon Alexa, Google Assistant and Samsung SmartThings smart home platforms.



¹ EASY INSTALLATION: Systems that require a common wire include heat-only and cool-only systems.

² ENERGY SAVINGS: Calculated by comparing operation time for a nationwide sample of Sensi users with temperature adjustments averaging 4° in comparison to users with no adjustments. Savings vary based on equipment type/condition, insulation, climate & temperature adjustment size/frequency.

Amazon, Alexa and all related logos are trademarks of Amazon.com, Inc. or its affiliates.

Google is a trademark of Google LLC.

Sensi Lite smart thermostat

SPECIFICATIONS



| | | | | | |
|--|---|--|------------------------------------|----------------------------------|--|
| ELECTRICAL RATING | RATED DIFFERENTIALS (@ 6°F / HR) | FAST | MED | SLOW | WIRELESS TECHNOLOGY |
| 20 to 30 VAC, 50/60 Hz 1.5 Amps maximum per terminal 2.5 Amps maximum (all terminals combined) | Heat (conventional gas/oil/elect): Cool (central air): Heat pump (heat and cool): Heat pump (aux): | 0.5°F 0.9°F 0.9°F 0.5°F | 0.75°F 1.2°F 1.2°F 0.75°F | 1.9°F 1.7°F 1.7°F 1.9°F | 2.4 Ghz Wi-Fi (802.11 a/b/g/n supported) Bluetooth Low Energy |
| STANDARD SYSTEMS | COMPATIBILITY | | | | DIMENSIONS |
| Single-stage gas, oil, electric Single-stage heat pump with AUX heat Two-stage gas, oil, electric Two-stage cooling | Conventional heating and cooling | Gas furnace Air conditioner Electric furnace Boiler | | | 5.1" W x 3.1" H x .88" D |
| SETPOINT RANGE | Heat only ¹ | Gas furnace Electric furnace Boiler | | | STORAGE |
| 45°F to 99°F (7°C to 37°C) | Cool only ¹ | Air conditioner | | | -20° to 150°F (-29° to 65°C) 0%–90% RH non-condensing |
| ACCESSORIES | Heat pump | Heat pump only Gas furnace Electric furnace | | | OPERATING AMBIENT |
| Wallplate: (white) SA6W (6.75" x 4.50") Wallplate: (black) SA6B (6.75" x 4.50") Thermostat guard: F29-0198 | SENSI ALERT | TRIGGER | | | 32°F to +105°F (0°C to +41°C) |
| The Sensi thermostat provides automatic dual fuel control without an outdoor sensor. A fossil fuel kit may be added if user selectable balance point settings are desired. | High temperature: | Above 99°F | | | HUMIDITY RANGE |
| | Low temperature: | Below 45°F | | | 90% non-condensing max |
| | High humidity: | Above 70% | | | DISPLAY TEMPERATURE RANGE |
| | Loss of heat/cool: | Temp goes up or down 5°F during cycle | | | 32°F to +99°F (0°C to 37°C) |
| | | | | | TITLE 24 COMPLIANT |
| | | | | | ENERGY STAR CERTIFIED |

| MODEL NUMBER | PROGRAMS | | STAGES BY SYSTEM | | | SYSTEM TYPE | APPLICATIONS | | | | | | | POWER SOURCE | SELECTABLE PERFORMANCE FEATURES | | | | | | | |
|--------------|-------------------|-------------------------|------------------------|-----------------------|---------------------|-------------|--|----------------------|-------------------|----------------------|------------|--|--------------------|--------------|---|--|--|-----------------|---|------------------------|------------------------------------|--|
| | Program Options | Periods Per Day Options | Single-Stage Heat/Cool | Multi-Stage Heat/Cool | Heat Pump Heat/Cool | | Universal, Single-Stage, Multi-Stage, Heat Pump* | Gas / Oil / Electric | 3 Wire Zone Valve | Millivolt Compatible | Economizer | Humidity Control (H)-Humidity / (D)-Dehumidify | Accessory Terminal | | Dual Fuel Heat, Pump Control, Logic (L), Outdoor Sensor (O) | Remote Sensor Options, Indoor (I), Outdoor (O) | Battery (B), Hardwire / Common (H), Power Sharing (PS) | Auto Changeover | Programmable Fan (PF), Circulating Fan (CC) | Filter Change Reminder | Energy Mgt. Recovery / Early Start | Total Keypad Lockout (T), Partial Keypad Lockout (P) |
| ST25U | 7, NP, Geofencing | 8 Max | 1/1 | 2/1 or 1/2 | 2/1 | ✓ | ✓ | ✓ | - | - | - | - | L | - | H, PS | ✓ | CC | ✓ | ✓ | T | ✓ | 2.25" LCD |

TERMINAL DESIGNATIONS



* Universal thermostats provide the flexibility to control Single-stage, Multi-stage or Heat Pump systems.

SENSI.EMERSON.COM

The Sensi logo is a trademark and service mark of Emerson Electric Co.

R-5680