

MCG-8MVR Technical Data Sheet

	AC RATING	125V/15A//1875W/60HZ
	HOUSING	ABS High Impact Plastic
	COLOR	Black
	SOCKETS (TOTAL)	8
	POWER CABLE TYPE / LENGTH (EXPOSED)	AWG 14/3 SJT / 4'
	POWER CABLE JACKET MATERIAL	PVC
	AC PLUG STYLE	NEMA 5-15 45° Angle Plug
	OVERLOAD PROTECTION	15A Circuit Breaker
	ON-OFF SWITCH	Yes
	POWER SAFETY SHUT DOWN	1 x 15A Thermal Fuses
	THERMAL PROTECTION FOR MOVs	1 x 15A Thermal Fuses
METAL OXIDE VARISTOR	L - N	1x20 mm Super+ 201KD@480J
	L - G	1x20 mm Super+ 201KD@480J
	N - G	1x20 mm Super+ 201KD@480J
	AC CIRCUIT TOTAL JOULES:	1400J
	MAXIMUM SPIKE CURRENT (TOTAL)	30,000A
	MAXIMUM SPIKE VOLTAGE	6KV
	MOV CLAMPING VOLTAGE	500V L-N, 500V L-G, N-G
	RESPONSE TIME <1 NANOSECOND	Yes
	SURGE INDICATOR (Protected)	Yes - 1 x Red
	GROUNDING INDICATOR (WIRE FAULT)	Yes - 1 X Green
EM1 / RF1 NOISE FILTER	X2 CAPACITOR	1 x 0.1uF
	COIL	N/A
	FREQUENCY	150K Hz ~ 30 Hz
	ATTENUATION	Up to 20 dB Reduction
	START CONTROL OUTLET POWER	16W~60W
	STANDBY POWER CONSUMPTION	<1W Idle Current Draw
	PACKAGING STYLE	Four-Color Carton
	USER MANUAL & WARRANTY SHEET	Enclosed
	BAR CODE LABEL ON CASE PACK	Yes = 8 5583 00051 3
	MASTER CARTON BAR CODE	Yes =
	CASEPACK QUANTITY	16 PCS - Master Carton
	STANDARD EXPORT CARTON DESIGN	Yes
	AGENCY CERTIFICATIONS	c UL us

BITS #	MCG-8MVR	Unit	Unit Dims (cm)			Qty	Color Box Dims (cm)			G. W
		Pcs	L	W	H	Pcs	L	W	H	KGS
DESCRIPTION		1	26.35	9.75	3.5	1	31.5	14	5	0.6
8 Outlet Advanced Power Strip, 1400J, 4ft SJT Cord, 45° Right Angle Plug	Unit	Unit Dims (in)			Master Carton	Master Carton Dims (cm)			G.W.	
		L	W	H	pcs	L	W	H	KGS	
	1	10.4	3.8	1.4	10	33.5	26.8	30	6.7	
	CONTAINER - 20'		QTY	7200		Inner Qty	Color Box Dims (in)			G.W.
	CONTAINER - 40'		QTY	14,400		pcs	L	W	H	LBS
	1	12.4	5.5	1.97	1.32					
	Master Carton	Master Carton Dims (in)			G.W.					
	pcs	L	W	H	LBS					
	10	13.2	10.6	11.8	15.0					
	Pallet Quantities	Cartons / Pallet	Cartons / Layer	Units / Layer	Pallet Weight					
	720	72	12	120	1078 Lbs.					

