



# DR120A3000 Whole House Dehumidifier

## SUBMITTAL SHEET

Job Name	
Engineer	
Mechanical Contractor	
Contractor's P.O. No.	
Representative	
Notes	

Model(s)	
DR120A3000	Qty.
Notes	
Approval	
Service	
Tag No.	

## DR120A3000 CAPACITIES AND PERFORMANCE

Part Number: DR120A3000

### Blower:

400 CFM @ 0.0 in. WG

295 CFM @ 0.6 in. WG

Supply Voltage: 120 VAC; 60 Hz.

Amps: 7.3 A

Power transformer to R/C terminals: 24 VAC, 0.85A

Energy Performance: 2.9 liters (6.1 pints) per kilowatt hour (KWH) energy

Refrigerant: R-410A

Operating Temp Range (outside cabinet): 34 – 135 °F (1.1 – 57.2 °C)

### Capacity:

63 pints/day (60 °F [15.6 °C], 60 %RH)

88 pints/day (70 °F [21.1 °C], 60 %RH)

120 pints/day (80 °F [26.7 °C], 60 %RH)

Coverage: Up to 3500 sq. ft.

### Duct Connections:

6 in. Supply Inlet

10 in. Round Inlet

10 in. Round Outlet

(ABS Plastic)

Filter Efficiency: Standard MERV-11

Drain Connection: 3/4 in. threaded female NPT, with attached 3/4 in. threaded male NPT

### Dimensions (See Fig. 1):

Length: 25-7/8 in. (without collars)

Width: 14-3/4 in.

Height: 20-1/2 in.

Collar Length: 3-1/8 in. (each)

Weight: 95 lbs (43.1 Kg)

### Shipping Specs:

Width: 19.3 in.

Height: 26 in.

Length: 35.8 in.

Weight: 104 lbs (47.2 Kg)

### Optional Parts

Replacement Filter: 50070171-002

Motorized Ventilation Damper: EARD6

Bypass Damper: SPRD10

ETL Listed per UL 60335-1, 60335-2-40, CSA C22.2 No. 60335-1 and 60335-2-40




Fig. 1. Dimensions in in. (mm).

Resideo Whole-House Dehumidifiers are designed to help maintain proper humidity levels in the home. Lower humidity levels feel more comfortable and helps safeguard against problems from excess moisture in the home such as mold, mildew, warped wood, peeling of paint, or musty odors. The DR120A3000 is Energy Star rated providing efficient and economical operation.

### Dehumidification

The Resideo DR120A3000 dehumidifier utilizes refrigeration and internal air circulation to cool the incoming air stream below its dew point. Water condenses and drains off the coil, sending drier air back into the house.

- Can remove up to 120 pints/day of moisture.
- Energy Star rated
- Multitude of external controller options
- Side ducted exhaust
- Reduced noise during operation
- MERV 11 air filtration

### Ventilation

The Resideo DR120A3000 has a separate control for ventilation, so the powerful onboard blower can be used to efficiently bring fresh air into the house even when dehumidification is not needed. The DR120A3000 has a 6" supply side damper that can be used to duct in air from the outside, or closed if not needed.

### Simplified Wiring

The Resideo DR120A3000 dehumidifiers can be controlled by a variety of 24-volt remote wired and wireless controls.

The DR120A3000 allows the use of a 24V normally closed float switch or water sensor to simplify installation in a drain pan. This will allow the external float switch to kill power to the compressor in the event of water blockage.

By using this Resideo literature, you agree that Resideo will have no liability for any damages arising out of your use or modification to, the literature. You will defend and indemnify Resideo, its affiliates and subsidiaries, from and against any liability, cost, or damages, including attorneys' fees, arising out of, or resulting from, any modification to the literature by you.



Resideo Technologies, Inc.  
1985 Douglas Drive North, Golden Valley, MN 55422  
1-800-468-1502  
33-00591-02 SA 01-24

www.resideo.com

© 2024 Resideo Technologies, Inc. All rights reserved.

The Honeywell Home trademark is used under license from Honeywell International, Inc. This product is manufactured by Resideo Technologies, Inc. and its affiliates.



33-00591-02