

1. CCT Range complies to ANSI C78.377-2008.
2. Thermally stable typical lumens (± 10%)
3. Rated life is based on 70% lumen maintenance, and engineering testing and probability analysis.
4. Equivalency based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.

Note: All Information consistent with IESNA LM-80-08 results and IESNA LM-79-08 testing completed by a qualified third party facility.  
Note: All lamps meet Energy Star® Integral LED Lamp requirements, and will be submitted for testing.

**Dimensions**

Model	MOL	Diameter
MR16	1.97"	1.97"

Note: Lamp shape conforms to ANSI C78.21-2003.  
Note: Designed to comply with RoHS Directive 2002/95/EC.

**Energy Savings**

Model No.	Energy Savings
L3/L6-MR16GU10D-4.5W	\$84

\*Actual Equivalent Replacement, based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.  
Note: Energy Savings based on using one bulb for 25,000 hr rated life at 11¢/kWh. Does not include maintenance and replacement lamp savings.

**INTERNAL DRIVER  
GU10 SERIES**



**3 THREE YEARS WARRANTY** **FC** **UL LISTED**

Model No.	Item name	Lumens <sup>2</sup> (lm)	Watts (w)	CCT <sup>1</sup> (k)	Efficacy (lm/w)	CRI	Lifetime <sup>3</sup> (h)	Beam Angle	Base type	Voltage (v)	Cerification	Dimmable	Equivalent <sup>4</sup> (w)
L3/L6-MR16GU10D-4.5W	MR16	300	4.5	3000	67	80	25000	40°	GU10	120V	UL, FCC,Rohs	YES	35
L3/L6-MR16GU10D-4.5W	MR16	300	4.5	5000	67	80	25000	40°	GU10	120V	UL, FCC,Rohs	YES	35

1. CCT Range complies to ANSI C78.377-2008.
2. Thermally stable typical lumens (± 10%)
3. Rated life is based on 70% lumen maintenance, and engineering testing and probability analysis.
4. Equivalency based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.

Note: All Information consistent with IESNA LM-80-08 results and IESNA LM-79-08 testing completed by a qualified third party facility.  
Note: All lamps meet Energy Star® Integral LED Lamp requirements, and will be submitted for testing.

**Dimensions**

Model	MOL	Diameter
MR16	1.97"	1.97"

Note: Lamp shape conforms to ANSI C78.21-2003.  
Note: Designed to comply with RoHS Directive 2002/95/EC.

**Energy Savings**

Model No.	Energy Savings
L3/L6-MR16GU5.3-4.5W	\$84

\*Actual Equivalent Replacement, based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.  
Note: Energy Savings based on using one bulb for 25,000 hr rated life at 11¢/kWh. Does not include maintenance and replacement lamp savings.

**INTERNAL DRIVER  
GU5.3 SERIES**



**3 THREE YEARS WARRANTY** **FC** **UL LISTED**

Model No.	Item name	Lumens <sup>2</sup> (lm)	Watts (w)	CCT <sup>1</sup> (k)	Efficacy (lm/w)	CRI	Lifetime <sup>3</sup> (h)	Beam Angle	Base type	Voltage (v)	Cerification	Dimmable	Equivalent <sup>4</sup> (w)
L3/L6-MR16GU5.3-4.5W	MR16	300	4.5	3000	67	80	25000	40°	GU5.3	12V	UL, FCC,Rohs	NO	35
L3/L6-MR16GU5.3-4.5W	MR16	300	4.5	5000	67	80	25000	40°	GU5.3	12V	UL, FCC,Rohs	NO	35