

Hand-Held Shower



BITS *Eco-Logical*® Shower-heads are designed and engineered for style, savings and function. The hand-held showerhead is highly-polished with a chrome-plated finish and has three spray settings: 9-jet turbo-spray, gentle shower and a combo spray. The shower-head is connected to a chrome style flexible hose for easy use and can be placed in a convenient swivel-ball bracket mounted to the water-supply pipe for use as a "fixed" shower-head. When not in use, the shower-head easily snaps into the attachment bracket.

Features

- Three spray settings: Turbo, Gentle Shower and Combo.
- Ergonomic handle.
- Chrome-style 6' flexible hose.
- Corrosion-resistant, engineering-plastic inner components assure long life.



Hand-Held Shower with Hose & Attachment Bracket

Model #	Finish	Flow Rate	WaterSense	Case Qty
BH-150CH	Chrome	1.5 GPM	Yes	12



Certification and Performance Standards

- CSA - USA & Canada
- WaterSense - Certified by CSA Group
- ASME A112.18.1

Miscellaneous Plumbing Items

Model #	Description	Size	Case Quantity
TT-30	PTFE Tape-Single Application	30" x 5/16"	500
WTC	Water Temperature Card	3 3/8" x 2 1/4"	500
WTC-1	Water Temp. Card - Custom	3 3/8" x 2 1/4"	500
FFW	Furnace Filter Whistle	1 1/2" x 1"	500

PTFE Tape



Temperature Card Front and Back

Save energy and money with

To test the temperature of your hot water, place the card under running water for 15 seconds.

Be sure that the black strip on the other side of the card is directly in the water stream.

If the water temperature is too hot, adjust the controls on the water heater and test again in 12 hours. Most controls are near the bottom of the water heater.

Lowering the temperature by just 10°F can lower your water heating cost by 3-5% saving you energy and money every month.

Water Temperature	Time it takes for a		
Degrees F	Degrees C	Mild Burn	Severe Burn
110	43	Normal Shower Temp.	
116	47	35 mins.	45 mins.
120	49	3 mins.	9 mins.
122	50	1 min.	5 mins.
126	52	30 secs.	80 secs.
131	55	5 secs.	25 secs.
140	60	2 secs.	5 secs.
149	65	1 sec.	2 secs.
154	68	Instantly	1 sec.

Maintaining a water temperature of 120°F or less in homes with small children and/or elderly and disabled is strongly recommended.

Temperature will appear after 15 seconds.

Furnace Filter Whistle



Specifications subject to change at any time without notice.

Warranty applies to manufacturer defects.

BITS will, at their sole option, repair or replace upon return of defective item.