



**ENERGETIC**  
L I G H T I N G

Project:		Catalog #:		Type:	
----------	--	------------	--	-------	--

Prepared by:		Notes:		Date:	
--------------	--	--------	--	-------	--

## SLA Series


LED Strip Light Fixture  
CCT & Wattage-Selectable • 4-ft & 8-ft options




### KEY FEATURES

- Compact and narrow design allow for various applications and use cases
- EZCCT field-selectable CCT - 3500K, 4000K & 5000K @ >80 CRI
- EZWATT field-selectable wattage allow option for reduced wattage for greater energy savings
- Energy efficient up to 130 lm/W
- Separate backplate housing for easy keyhole mounting
- Suitable for dry or damp location installations
- Dimmable down to 10% with 0-10v input standard
- Optional motion sensor or battery backup available
- Available in 4-ft and 8-ft options

### Highlights



Hands-free support cable on inner LED plate speeds up installation time and effort




Conduit knockout options available on both ends (1/2" and 1/4" trade-sizes) as well as three 1/2" locations on back plate



Matching white junction box faceplate available to cover up exposed opening



Energetic Lighting's ezCCT and ezWatt feature allow user-selectable color temperature and wattage



Accessible inner wiring compartment tray for easy wire routing without light path interference

### Load Information

<b>Input Voltage</b>	120-277Vac	
<b>Power Factor</b>	0.9	
<b>THD</b>	20%	
<b>Low Temp Start</b>	-25°C (-13°F)	
<b>Max Temp</b>	45°C (113°F)	
<b>Unit Weight</b>	4-ft profile	tba
	8-ft profile	tba

### Shipping Information



Item	Weight	Box Qty.
4-ft profile	tba lbs	6 per
8-ft profile	tba lbs	6 per

### Lumen Maintenance



Ambient Temp	TM-21 Lumen Maint. (50,000 hours)	Theoretical L70 (hours)
25°C	>70%	50,000

### Dimensions

4-ft profile  
SLAM4NS52SE83550



8-ft profile  
SLAM8NS104SE83550



**Specifications**

Catalog Logic	Order #	Lumens	Wattage	LPW	Color Temperature	CRI	Voltage	Dimming	Certifications	Pallet Qty
SLAM4NS52SE83550	30214	5200   4550   3900 selectable	40   35   30 selectable	130	3500K, 4000K, 5000K selectable	80	120- 277Vac	0-10v	ETL, DLC	TBA
SLAM8NS104SE83550	30215	10400   9150   7800 selectable	60   70   80 selectable	130	3500K, 4000K, 5000K selectable	80	120- 277Vac	0-10v	ETL, DLC	TBA

**Photometric Data**



**ENERGETIC**  
L I G H T I N G

## SLA Series

LED Strip Light Fixture  
CCT&Wattage-Selectable • 4-ft & 8-ft options

### NOTES: