

# EGC-7MVR Technical Data Sheet

	AC RATING	125V/15A//1875W/60HZ
	HOUSING	ABS High Impact Plastic
	COLOR	Black
	SOCKETS (TOTAL)	7
	POWER CABLE TYPE / LENGTH (EXPOSED)	AWG 14/3 SJT / 3'
	POWER CABLE JACKET MATERIAL	PVC
	AC PLUG STYLE	NEMA 5-15 Right Angle Plug
	OVERLOAD PROTECTION	15A Circuit Breaker
	ON-OFF SWITCH	No
	POWER SAFETY SHUT DOWN	1 x 15A Thermal Fuses
	THERMAL PROTECTION FOR MOVs	1 x 15A Thermal Fuses
METAL OXIDE VARISTOR	L - N	2x20 mm 201KD@350J+
	L - G	1x20 mm 201KD@350J+
	N - G	1x20 mm 201KD@350J+
	AC CIRCUIT TOTAL JOULES:	1400J
	MAXIMUM SPIKE CURRENT (TOTAL)	37,000A
	MAXIMUM SPIKE VOLTAGE	6KV
	MOV CLAMPING VOLTAGE	400V L-N, 500V L-G, N-G
	RESPONSE TIME <1 NANOSECOND	Yes
	SURGE INDICATOR (Protected)	Yes - 1 x Red
	GROUNDING INDICATOR (WIRE FAULT)	Yes - 1 X Green
EM1 / RF1 NOISE FILTER	X2 CAPACITOR	1 x 0.1uF
	COIL	N/A
	FREQUENCY	100K Hz ~ 50M Hz
	ATTENUATION	Up to 50 dB Reduction
	START CONTROL OUTLET POWER	16W~60W
	STANDBY POWER CONSUMPTION	<1W Idle Current Draw
	PACKAGING STYLE	Four-Color Carton
	USER MANUAL & WARRANTY SHEET	Enclosed
	BAR CODE LABEL ON CASE PACK	Yes = 8 5583 00006 3
	MASTER CARTON BAR CODE	Yes =
	CASEPACK QUANTITY	16 PCS - Master Carton
	STANDARD EXPORT CARTON DESIGN	Yes
	AGENCY CERTIFICATIONS	c UL us

BITS #	EGC-7MVR	Unit	Unit Dims (cm)			Qty	Color Box Dims (cm)			G. W
		P	L	W	H	pcs	L	W	H	KGS
DESCRIPTION		1	31.5	7.1	3.8	1	36.0	11.0	5.0	0.54
7 Outlet Advanced Power Strip, 1400J, 3ft SJT Cord, Right Angle Plug	Unit	Unit Dims (in)			Master Carton	Master Carton Dims (cm)			G.W.	
		L	W	H	pcs	L	W	H	KGS	
	1	12.5	2.75	1.5	16	40.4	23.8	37.6	9.5	
	CONTAINER - 20'		QTY	12,160		Inner Qty	Color Box Dims (in)			G.W.
	CONTAINER - 40'		QTY	24,640		pcs	L	W	H	LBS
						14.125	4.375	1.9	1.19	
		Master Carton	Master Carton Dims (in)			G.W.				
		pcs	L	W	H	LBS				
		16	15.9	9.375	14.8	20.9				
		Pallet Quantities	Cartons / Pallet	Cartons / Layer	Units / Layer	Pallet Weight				
		576	36	12	192	792				

