



TOPSTAR HID LED lamp replaces a 70-400W HID and is suitable for use in totally enclosed fixtures. Its high lumen output and exceptional efficacy make it an ideal choice for outdoor post top applications. The special designed heat sink system allows air to flow freely through the lamp. It uses an increased cooling surface area to reduce the operating temperature of the LED and power supply, thus resulting in longer lamp life and lumen maintenance.

- 70W-400W HID replacement
- Direct line voltage 120-277V - Not compatible with ballasts
- Designed for use in post top applications
- Available in 4000K & 5000K CCT
- Suitable for use in totally enclosed fixtures
- 5 years warranty
- DLC 4.3 Listed

Ordering Code	Watt (W)	Initial Lumen *	Base **	CRI	Color Temp.	Rated Average life	MOD (in.)	MOL (in.)	Beam Angle
CNE26-8YY-36P-M1/M2-BP	36	4320	E26	82	5000K	50,000	3.74	8.15	360
● CNE39-8YY-36P-M1/M2-BP	36	4320	E39	82	5000K	50,000	3.74	8.46	360
● CNEX39-8YY-54P-M1/M2-BP	54	6480	EX39	82	5000K	50,000	3.74	10.43	360
● CNEX39-8YY-75P-M1/M2-BP	75	9000	EX39	82	5000K	50,000	3.74	12.05	360
● CNEX39-8YY-100P-M1/M2-BP	100	15000	EX39	82	5000K	50,000	5.51	9.92	360

- DLC 4.3 Listed
- Initial lumen is @ 5000K
- ** EX39 is compatible with E39

Note: This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:(1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause un desired operation.

Suitable for use in enclosed luminaires. This device is not intended for use with emergency exits.