



Dimmable LED Downlight

Ordering Information


Model No.	Item name	Lumens ² (lm)	Watts (w)	CCT ¹ (k)	Efficacy (lm/w)	CRI	Lifetime ³ (h)	Base type	Voltage (v)	Cerification	Equivalent ⁴ (w)
L12-DL6DWP-15W	Downlight	1200	15	5000K	80	80	35000	E26	120	UL, ES	75



1. CCT Range complies to ANSI C78.377-2008.
 2. Thermally stable typical lumens (± 10%)
 3. Rated life is based on 70% lumen maintenance, and engineering testing and probability analysis.
 4. Equivalency based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.
 5. Energy Star® will be available in Q2,2016.
- Note: All Information consistent with IESNA LM-80-08 results and IESNA LM-79-08 testing completed by a qualified third party facility.
 Note: All lamps meet Energy Star® Integral LED Lamp requirements, and has been submitted for testing.

Dimensions

Model	MOL	Diameter
5"/6"Downlight(L11)	2.11"	7.48"



- Note: Lamp shape conforms to ANSI C78.21-2003.
 Note: Designed to comply with RoHS Directive 2002/95/EC.

Energy Savings

Model No.	Equivalent	Energy Savings
L12-DL6DWP-15W	75W Incandescent	\$219

*Actual Equivalent Replacement, based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.
 Note: Energy Savings based on using one bulb for 25,000 hr rated life at 11¢/kWh. Does not include maintenance and replacement lamp savings.