



PERFORMANCE FEATURES

- Creative polygonal diamond design, breaking the traditional design
- Die-cast aluminium shell, stable and durable
- The lower light output is a transparent flat lens so light output is concentrated and uniform
- Easy installation and maintenance
- ETL Certification, 5 years warranty.
- 4W EM Battery Backup provides 90 min emergency run time (-EM)

WPS

Construction	Aluminum + Glass
Finish	Bronze
Warranty	5 year Warranty
Application	Building exterior walls, corridor aisles, Safety passages, Entrance passages.

SKU GUIDE

Model Section → WPS-12W-XXK-BZ					
Power	Luminous flux	Efficacy (Lm/W)	Power Factor	Surge Protection	Mount height
12W	1480 Lm	121 Lm/W	0.9	2 KV	10ft

WPS-12W-XXK-BZ				
Dimming	Distribution	Dimension	Mounting	Controls
0-10V	Type III, Full-cut-off	147x98x193.5mm	Junction Box Mounting	Photocell (120V-277V) (optional)

Model Section → WPS-18W-XXK-BZ					
Power	Luminous flux	Efficacy (Lm/W)	Power Factor	Surge Protection	Mount height
18W	2310 Lm	120 Lm/W	0.9	2 KV	10ft

WPS-18W-XXK-BZ				
Dimming	Distribution	Dimension	Mounting	Controls
0-10V	Type III, Full-cut-off	147x98x193.5mm	Junction Box Mounting	Photocell (120V-277V) (optional)

Model Section WPS-28W-XXK-BZ					
Power	Luminous flux	Efficacy (Lm/W)	Power Factor	Surge Protection	Mount height
28W	3350 Lm	120 Lm/W	0.9	2 KV	12ft

WPS-28W-XXK-BZ				
Dimming	Distribution	Dimension	Mounting	Controls
0-10V	Type III, Full-cut-off	147x98x193.5mm	Junction Box Mounting	Photocell (120V-277V) (optional)

ENERGY CONSUMPTION		
	Max.	Max. with heater
120VAC, 60Hz	3.59W	3.40W
277VAC, 60Hz	3.59W	3.40W

WPS-28W-XXK-BZ		
Dimming	Dimension	Mounting
0-10V	192x143x97 mm	Junction Box Mounting

PRODUCT DIMENSIONS

