

For quick, easy, and affordable LED upgrades, switch to TCP's LED Downlights. TCP downlights have both E26 and direct wire options, PMMA plastic to prevent lens discoloration, and quick snap holding arms to quickly attach to a recessed can. With the classic beveled look, these downlights provide smooth even light in the color temperature you need.

Reasons to choose the LED Beveled Selectable Recessed Downlights from TCP

- Long, 35,000 hour life minimizes replacement and maintenance costs
- Excellent color consistency and CRI enhances colors of the focal point while maintaining uniformity throughout lighting installation
- Very low heat generation makes the downlight perfect for sensitive display lighting
- Durable PMMA plastic housing prevents discoloration
- Easy installation that mounts directly to either a 4" or 6" recessed can, as well as both E26 and direct wire power options
- Smooth, uniform dimming from 100 5%
- Select between 3000K, 4000K, and 5000K
- 5"/6" product also allows for wattage selectivity

Ideal Applications

Commercial

Retail

Healthcare

Industrial

TCP[®]

Residential

Specifications:

Color Temperatures	3000K, 4100K, 5000K
Wattage options	4": 11W
	5"/6": 8W, 10.5W, 14.5W
Input Line Voltage	120 VAC
Input Line Frequency	50/60HZ
Lamp Life (Rated)	35,000 hours

Minimum Starting Temp	22°F/-30°C
Maximum Operating Temp	
CRI	
IC-rated for direct contact with insulation	

UL approved for damp location (indoor only)—outdoor environment may cause yellowing of the white trim. This is not covered by warranty.







LED Beveled Selectable Recessed Downlight

Specifications:



ITEM #	DESCRIPTION	VOLTAGE	WATTS	INCANDES. WATTS	LPW	LUMENS	COLOR	CRI	MOL (inches)	DIA (inches)	BEAM ANGLE	BASE	WARRANTY YEARS
LED 75W Equivalent Options													
DR4 Downlight • Dimmable • 35,000 Hour													
L75DR4DCCT2	4" LED Color Selectable Beveled Downlight	120V	11	75	112.5/120/114	900/960/915	3000K/4000K/5000K	80	3.0	5	90°	E26	5
LED 120W Equivalent Options DR56 Downlight • Dimmable • 35,000 Hour													
L120DR56DCCT2	5"/6" LED Color & Wattage Selectable Beveled Downlight	120V	8/10.5/14.5	120	8W: 113.8/118.1/115 10.5W: 104.8/110.5/106.7 14.5W: 100/94.5/102.8	8W: 910/945/920 10.5W: 1100/1160/1120 14.5W: 1450/1370/1490	3000K/4000K/5000K	80	3.0	7.4	90°	E26	5

