



# LED Elite PAR Lamps

## Product Specifications



TCP's award winning PAR lamps combine traditional beauty with top-notch technology. With the wide variety of options available—you can be sure to find the PAR lamps to meet your needs.

### Reasons to choose the LED Elite PAR Lamps from TCP

- Provides instant energy savings by using up to 85% less energy than halogen alternatives
- Long 25,000 hour rated life minimizes replacement and maintenance costs
- Unique full face optics provide designer grade light quality with the same look as halogen replacements
- Light weight means track and downlight installations are not strained by excess weight
- UL approved for wet locations
- Smooth clean outside housing blends into lighting applications
- Durable plastic lowers the risk for injury or breakage

### Ideal Applications

- Track lights
- Recessed downlights
- Retail merchandising applications
- Display lights
- Flood and spotlighting

### Specifications

Color Temperatures.....2400K, 2700K, 3000K, 3500K, 4100K, 5000K  
 Wattage Replacements..... 50W, 60W, 75W, 90W, 120W, 150W  
 Input Line Voltage ..... 120 VAC  
 Input Line Frequency..... 50/60HZ

Lamp Life (Rated) .....25,000 hours  
 Minimum Starting Temp ..... -30°C/-22°F  
 Maximum Operating Temp.....45°C/113°F  
 CRI..... 80

Approved for enclosed fixtures however completely sealed fixture applications (ex: in ground landscape fixtures) may reduce life.



## Specifications

ITEM #	DESCRIPTION	WATTS	LUMENS	CRI	LPW	MEASURED CBCP	COLOR TEMP	BEAM ANGLE	BASE	MOL (IN.)	DIA (IN.)	WARRANTY YEARS	# IN CASE
<b>LED 7W PAR20 Lamps – Dimmable • 25,000 Hours</b>													
LED8P20D24KFL	LED 7W P20 DIM 24KFL	7	450	80	64.3	1058	2400K	40°	E26	3.5	2.5	5	12
LED8P20D24KNFL	LED 7W P20 DIM 24KNFL	7	450	80	64.3	1894	2400K	25°	E26	3.5	2.5	5	12
LED8P20D27KFL	LED 7W P20 DIM 27KFL	7	525	80	75	1208	2700K	40°	E26	3.5	2.5	5	12
LED8P20D27KFLB	LED 7W P20 DIM 27KFL BLACK	7	525	80	75	1208	2700K	40°	E26	3.5	2.5	5	12
LED8P20D27KNFL	LED 7W P20 DIM 27KNFL	7	525	80	75	2030	2700K	25°	E26	3.5	2.5	5	12
LED8P20D30KFL	LED 7W P20 DIM 30KFL	7	525	80	75	1187	3000K	40°	E26	3.5	2.5	5	12
LED8P20D30KFLB	LED 7W P20 DIM 30KFL BLACK	7	525	80	75	1187	3000K	40°	E26	3.5	2.5	5	12
LED8P20D30KNFL	LED 7W P20 DIM 30KNFL	7	525	80	75	2050	3000K	25°	E26	3.5	2.5	5	12
LED8P20D30KNFLB	LED 7W P20 DIM 30KNFL BLACK	7	525	80	75	2050	3000K	25°	E26	3.5	2.5	5	12
LED8P20D35KFL	LED 7W P20 DIM 35KFL	7	525	80	75	1131	3500K	40°	E26	3.5	2.5	5	12
LED8P20D35KNFL	LED 7W P20 DIM 35KNFL	7	525	80	75	-	3500K	25°	E26	3.5	2.5	5	12
LED8P20D41KFL	LED 7W P20 DIM 41KFL	7	525	80	75	1383	4100K	40°	E26	3.5	2.5	5	12
LED8P20D41KFLB	LED 7W P20 DIM 41KFL BLACK	7	525	80	75	1383	4100K	40°	E26	3.5	2.5	5	12
LED8P20D41KNFL	LED 7W P20 DIM 41KNFL	7	525	80	75	2174	4100K	25°	E26	3.5	2.5	5	12
LED8P20D41KNFLB	LED 7W P20 DIM 41KNFL BLACK	7	525	80	75	2174	4100K	25°	E26	3.5	2.5	5	12
LED8P20D50KFL	LED 7W P20 DIM 50KFL	7	525	80	75	1330	5000K	40°	E26	3.5	2.5	5	12
LED8P20D50KFLB	LED 7W P20 DIM 50KFL BLACK	7	525	80	75	1330	5000K	40°	E26	3.5	2.5	5	12
LED8P20D50KNFL	LED 7W P20 DIM 50KNFL	7	525	80	75	2172	5000K	25°	E26	3.5	2.5	5	12
<b>LED 10W PAR30 Short Neck Lamps – 60W Equiv. • Dimmable • 25,000 Hours</b>													
LED10P30SD27KFL	LED 10W P30 DIM 27KFL	10	720	80	72	1714	2700K	40°	E26	3.6	3.8	5	12
LED10P30SD27KNFL	LED 10W P30 DIM 27KNFL	10	720	80	72	3051	2700K	25°	E26	3.6	3.8	5	12
LED10P30SD30KFL	LED 10W P30 DIM 30KFL	10	720	80	72	1621	3000K	40°	E26	3.6	3.8	5	12
LED10P30SD30KFLB	LED 10W P30SN DIM 30KFL BLACK	10	720	80	72	1621	3000K	40°	E26	3.6	3.8	5	12
LED10P30SD30KNFL	LED 10W P30 DIM 30KNFL	10	720	80	72	3064	3000K	25°	E26	3.6	3.8	5	12
LED10P30SD30KSP	LED 10W P30 DIM 30KSP	10	720	80	72	-	3000K	15°	E26	3.6	3.8	5	12
LED10P30SD41KFL	LED 10W P30 DIM 41KFL	10	720	80	72	1847	4100K	40°	E26	3.6	3.8	5	12
<b>LED 10W PAR30 Short Neck Lamps – 75W Equiv. • Dimmable • 25,000 Hours</b>													
LED12P30SD30KNFL	LED 10W P30SN DIM 30KNFL	10	850	80	85	4968	3000K	25°	E26	3.6	3.8	5	12
LED12P30SD30KNFLB	LED 10W P30SN DIM 30KNFL BLACK	10	850	80	85	4968	3000K	25°	E26	3.6	3.8	5	12
LED12P30SD30KSP	LED 10W P30SN DIM 30KSP	10	850	80	85	8380	3000K	40°	E26	3.6	3.8	5	12
LED12P30SD30KSPB	LED 10W P30SN DIM 30KSP BLACK	10	850	80	85	8380	3000K	15°	E26	3.6	3.8	5	12
LED12P30SD35KFL	LED 10W P30SN DIM 35KFL	10	850	80	85	2232	3500K	15°	E26	3.6	3.8	5	12
LED12P30SD35KFLB	LED 10W P30SN DIM 35KFL BLACK	10	850	80	85	2232	3500K	40°	E26	3.6	3.8	5	12
LED12P30SD35KNFL	LED 10W P30SN DIM 35KNFL	10	850	80	85	4402	3500K	25°	E26	3.6	3.8	5	12
LED12P30SD35KNFLB	LED 10W P30SN DIM 35KNFL BLACK	10	850	80	85	4402	3500K	25°	E26	3.6	3.8	5	12
LED12P30SD35KSP	LED 10W P30SN DIM 35KSP	10	850	80	85	-	3500K	15°	E26	3.6	3.8	5	12

## Specifications

ITEM #	DESCRIPTION	WATTS	LUMENS	CRI	LPW	MEASURED CBCP	COLOR TEMP	BEAM ANGLE	BASE	MOL (IN.)	DIA (IN.)	WARRANTY YEARS	# IN CASE
<b>LED 10W PAR30 Short Neck Lamps – 75W Equiv. • Dimmable • 25,000 Hours</b>													<i>continued...</i>
ED12P30SD41KFL	LED 10W P30SN DIM 41KFL	10	850	80	85	2247	4100K	40°	E26	3.6	3.8	5	12
LED12P30SD41KFLB	LED 10W P30SN DIM 41KFL BLACK	10	850	80	85	2247	4100K	40°	E26	3.6	3.8	5	12
LED12P30SD41KNFL	LED 10W P30SN DIM 41KNFL	10	850	80	85	4895	4100K	25°	E26	3.6	3.8	5	12
LED12P30SD41KSP	LED 10W P30SN DIM 41KSP	10	850	80	85	8710	4100K	15°	E26	3.6	3.8	5	12
LED12P30SD50KFL	LED 10W P30SN DIM 50KFL	10	850	80	85	2454	5000K	40°	E26	3.6	3.8	5	12
LED12P30SD50KNFL	LED 10W P30SN DIM 50KNFL	10	850	80	85	5260	5000K	25°	E26	3.6	3.8	5	12
LED12P30SD50KSP	LED 10W P30SN DIM 50KSP	10	850	80	85	9292	5000K	15°	E26	3.6	3.8	5	12
<b>LED 10.5W PAR30 Lamps – 75W Equiv. • Dimmable • 25,000 Hours</b>													
LED12P30D24KFL	LED 10.5W P30 DIM 24KFL	10.5	850	80	76.2	-	2400K	40°	E26	4.6	3.8	5	12
LED12P30D24KNFL	LED 10.5W P30 DIM 24KNFL	10.5	850	80	76.2	-	2400K	25°	E26	4.6	3.8	5	12
LED12P30D24KSP	LED 10.5W P30 DIM 24KSP	10.5	850	80	76.2	-	2400K	15°	E26	4.6	3.8	5	12
LED12P30D27KFL	LED 10.5W P30 DIM 27KFL	10.5	850	80	81	2202	2700K	40°	E26	4.6	3.8	5	12
LED12P30D27KFLB	LED 10.5W P30 DIM 27KFL BLACK	10.5	850	80	81	2202	2700K	40°	E26	4.6	3.8	5	12
LED12P30D27KNFL	LED 10.5W P30 DIM 27KNFL	10.5	850	80	81	5031	2700K	25°	E26	4.6	3.8	5	12
LED12P30D27KNFLB	LED 10.5W P30SN DIM 27KNFL BLACK	10.5	850	80	81	5031	2700K	25°	E26	4.6	3.8	5	12
LED12P30D27KSP	LED 10.5W P30 DIM 27KSP	10.5	850	80	81	9193	2700K	15°	E26	4.6	3.8	5	12
LED12P30D27KSPB	LED 10.5W P30 DIM 27KSP BLACK	10.5	850	80	81	9193	2700K	15°	E26	4.6	3.8	5	12
LED12P30D30KFL	LED 10.5W P30 DIM 30KFL	10.5	850	80	81	2389	3000K	40°	E26	4.6	3.8	5	12
LED12P30D30KFLB	LED 10.5W P30 DIM 30KFL BLACK	10.5	850	80	81	2389	3000K	40°	E26	4.6	3.8	5	12
LED12P30D30KNFL	LED 10.5W P30 DIM 30KNFL	10.5	850	80	81	5528	3000K	25°	E26	4.6	3.8	5	12
LED12P30D30KNFLB	LED 10.5W P30 DIM 30KNFL BLACK	10.5	850	80	81	5528	3000K	25°	E26	4.6	3.8	5	12
LED12P30D30KSP	LED 10.5W P30 DIM 30KSP	10.5	850	80	81	9006	3000K	15°	E26	4.6	3.8	5	12
LED12P30D30KSPB	LED 10.5W P30 DIM 30KSP BLACK	10.5	850	80	81	9006	3000K	15°	E26	4.6	3.8	5	12
LED12P30D35KFL	LED 10.5W P30 DIM 35KFL	10.5	850	80	81	-	3500K	40°	E26	4.6	3.8	5	12
LED12P30D35KNFL	LED 10.5W P30 DIM 35KNFL	10.5	850	80	81	-	3500K	25°	E26	4.6	3.8	5	12
LED12P30D35KSP	LED 10.5W P30 DIM 35KSP	10.5	850	80	81	-	3500K	15°	E26	4.6	3.8	5	12
LED12P30D41KFL	LED 10.5W P30 DIM 41KFL	10.5	850	80	81	2561	4100K	40°	E26	4.6	3.8	5	12
LED12P30D41KFLB	LED 10.5W P30 DIM 41KFL BLACK	10.5	850	80	81	2561	4100K	40°	E26	4.6	3.8	5	12
LED12P30D41KNFL	LED 10.5W P30 DIM 41KNFL	10.5	850	80	81	5781	4100K	25°	E26	4.6	3.8	5	12
LED12P30D41KNFLB	LED 10.5W P30 DIM 41KNFL BLACK	10.5	850	80	81	5781	4100K	25°	E26	4.6	3.8	5	12
LED12P30D41KSP	LED 10.5W P30 DIM 41KSP	10.5	850	80	81	9491	4100K	15°	E26	4.6	3.8	5	12
LED12P30D41KSPB	LED 10.5W P30 DIM 41KSP BLACK	10.5	850	80	81	9491	4100K	15°	E26	4.6	3.8	5	12
LED12P30D50KFL	LED 10.5W P30 DIM 50KFL	10.5	850	80	81	2437	5000K	40°	E26	4.6	3.8	5	12
LED12P30D50KFLB	LED 10.5W P30 DIM 50KFL BLACK	10.5	850	80	81	2437	5000K	40°	E26	4.6	3.8	5	12
LED12P30D50KNFL	LED 10.5W P30 DIM 50KNFL	10.5	850	80	81	5575	5000K	25°	E26	4.6	3.8	5	12
LED12P30D50KSP	LED 10.5W P30 DIM 50KSP	10.5	850	80	81	9647	5000K	15°	E26	4.6	3.8	5	12

## Specifications

ITEM #	DESCRIPTION	WATTS	LUMENS	CRI	LPW	MEASURED CBCP	COLOR TEMP	BEAM ANGLE	BASE	MOL (IN.)	DIA (IN.)	WARRANTY YEARS	# IN CASE
<b>LED 13.5W PAR30 Lamps – 75W Equiv. • Dimmable • 25,000 Hours</b>													
LED14P30D24KFL	LED 13.5W P30 DIM 24KFL	13.5	1000	80	74.1	-	2400K	40°	E26	4.6	3.8	5	12
LED14P30D24KNFL	LED 13.5W P30 DIM 24KNFL	13.5	1000	80	74.1	-	2400K	25°	E26	4.6	3.8	5	12
LED14P30D24KNFLB	LED 13.5W P30 DIM 24KNFL BLACK	13.5	1000	80	74.1	-	2400K	25°	E26	4.6	3.8	5	12
LED14P30D24KSP	LED 13.5W P30 DIM 24KSP	13.5	1000	80	74.1	-	2400K	15°	E26	4.6	3.8	5	12
LED14P30D27KFL	LED 13.5W P30 DIM 27KFL	13.5	1050	80	77.8	2693	2700K	40°	E26	4.6	3.8	5	12
LED14P30D27KFLB	LED 13.5W P30 DIM 27KFL BLACK	13.5	1050	80	77.8	2693	2700K	40°	E26	4.6	3.8	5	12
LED14P30D27KNFL	LED 13.5W P30 DIM 27KNFL	13.5	1050	80	77.8	5808	2700K	25°	E26	4.6	3.8	5	12
LED14P30D27KNFLB	LED 13.5W P30 DIM 27KNFL BLACK	13.5	1050	80	77.8	5808	2700K	25°	E26	4.6	3.8	5	12
LED14P30D27KSP	LED 13.5W P30 DIM 27KSP	13.5	1050	80	77.8	10563	2700K	15°	E26	4.6	3.8	5	12
LED14P30D27KSPB	LED 13.5W P30 DIM 27KSP BLACK	13.5	1050	80	77.8	10563	2700K	15°	E26	4.6	3.8	5	12
LED14P30D30KFL	LED 13.5W P30 DIM 30KFL	13.5	1050	80	77.8	2849	3000K	40°	E26	4.6	3.8	5	12
LED14P30D30KFLB	LED 13.5W P30 DIM 30KFLB	13.5	1050	80	77.8	2849	3000K	40°	E26	4.6	3.8	5	12
LED14P30D30KNFL	LED 13.5W P30 DIM 30KNFL	13.5	1050	80	77.8	6392	3000K	25°	E26	4.6	3.8	5	12
LED14P30D30KNFLB	LED 13.5W P30 DIM 30KNFL BLACK	13.5	1050	80	77.8	6392	3000K	25°	E26	4.6	3.8	5	12
LED14P30D30KSP	LED 13.5W P30 DIM 30KSP	13.5	1050	80	77.8	11181	3000K	15°	E26	4.6	3.8	5	12
LED14P30D30KSPB	LED 13.5W P30 DIM 30KSP BLACK	13.5	1050	80	77.8	11181	3000K	15°	E26	4.6	3.8	5	12
LED14P30D35KFL	LED 13.5W P30 DIM 35KFL	13.5	1050	80	77.8	-	3500K	40°	E26	4.6	3.8	5	12
LED14P30D35KFLB	LED 13.5W P38 DIM 35KFL BLACK	13.5	1050	80	77.8	-	3500K	40°	E26	4.6	3.8	5	12
LED14P30D35KNFL	LED 13.5W P30 DIM 35KNFL	13.5	1050	80	77.8	-	3500K	25°	E26	4.6	3.8	5	12
LED14P30D35KSP	LED 13.5W P38 DIM 35KSP	13.5	1050	80	77.8	-	3500K	15°	E26	4.6	3.8	5	12
LED14P30D41KFL	LED 13.5W P30 DIM 41KFL	13.5	1050	80	77.8	2661	4100K	40°	E26	4.6	3.8	5	12
LED14P30D41KFLB	LED 13.5W P30 DIM 41KFL BLACK	13.5	1050	80	77.8	2661	4100K	40°	E26	4.6	3.8	5	12
LED14P30D41KNFL	LED 13.5W P30 DIM 41KNFL	13.5	1050	80	77.8	5781	4100K	25°	E26	4.6	3.8	5	12
LED14P30D41KNFLB	LED 13.5W P30 DIM 41KNFL BLACK	13.5	1050	80	77.8	5781	4100K	25°	E26	4.6	3.8	5	12
LED14P30D41KSP	LED 13.5W P30 DIM 41KSP	13.5	1050	80	77.8	12465	4100K	15°	E26	4.6	3.8	5	12
LED14P30D41KSPB	LED 13.5W P30 DIM 41KSP BLACK	13.5	1050	80	77.8	12465	4100K	15°	E26	4.6	3.8	5	12
LED14P30D50KFL	LED 13.5W P38 DIM 50KFL	13.5	1050	80	77.8	2837	5000K	40°	E26	4.6	3.8	5	12
LED14P30D50KFLB	LED 13.5W P38 DIM 50KFL BLACK	13.5	1050	80	77.8	2837	5000K	40°	E26	4.6	3.8	5	12
LED14P30D50KNFL	LED 13.5W P30 DIM 50KNFL	13.5	1050	80	77.8	5875	5000K	25°	E26	4.6	3.8	5	12
LED14P30D50KSP	LED 13.5W P38 DIM 50KSP	13.5	1050	80	77.8	12073	5000K	15°	E26	4.6	3.8	5	12
<b>LED 13.5W PAR38 Lamps – 90W Equiv. • Dimmable • 25,000 Hours</b>													
LED14P38D24KFL	LED 13.5W P38 DIM 24KFL	13.5	1000	80	74.1	-	2400K	40°	E26	5.3	4.8	5	12
LED14P38D24KNFL	LED 13.5W P38 DIM 24KNFL	13.5	1000	80	74.1	-	2400K	25°	E26	5.3	4.8	5	12
LED14P38D24KSP	LED 13.5W P38 DIM 24KNFL	13.5	1000	80	74.1	-	2400K	25°	E26	5.3	4.8	5	12
LED14P38D27KFL	LED 13.5W P38 DIM 27KFL	13.5	1050	80	77.8	2480	2700K	40°	E26	5.3	4.8	5	12
LED14P38D27KNFL	LED 13.5W P38 DIM 27KNFL	13.5	1050	80	77.8	7649	2700K	25°	E26	5.3	4.8	5	12
LED14P38D27KNFLB	LED 13.5W P38 DIM 27KNFL BLACK	13.5	1050	80	77.8	7649	2700K	25°	E26	5.3	4.8	5	12

## Specifications

ITEM #	DESCRIPTION	WATTS	LUMENS	CRI	LPW	MEASURED CBCP	COLOR TEMP	BEAM ANGLE	BASE	MOL (IN.)	DIA (IN.)	WARRANTY YEARS	# IN CASE
<b>LED 13.5W PAR38 Lamps – 90W Equiv. • Dimmable • 25,000 Hours</b>													<i>continued....</i>
LED14P38D27KSP	LED 13.5W P38 DIM 27KSP	13.5	1050	80	77.8	12073	2700K	15°	E26	5.3	4.8	5	12
LED14P38D27KSPB	LED 13.5W P38 DIM 27KSP BLACK	13.5	1050	80	77.8	12073	2700K	15°	E26	5.3	4.8	5	12
LED14P38D30KFL	LED 13.5W P38 DIM 30KFL	13.5	1050	80	77.8	2498	3000K	40°	E26	5.3	4.8	5	12
LED14P38D30KNFL	LED 13.5W P38 DIM 30KNFL	13.5	1050	80	77.8	7606	3000K	25°	E26	5.3	4.8	5	12
LED14P38D30KSP	LED 13.5W P38 DIM 30KSP	13.5	1050	80	77.8	11845	3000K	15°	E26	5.3	4.8	5	12
LED14P38D30KWFL	LED 13.5W P38 DIM 30KWFL	13.5	1050	80	77.8	-	3000K	60°	E26	5.3	4.8	5	12
LED14P38D35KFL	LED 13.5W P38 DIM 35KFL	13.5	1050	80	77.8	-	3500K	15°	E26	5.3	4.8	5	12
LED14P38D35KFLB	LED 13.5W P38 DIM 35KFL BLACK	13.5	1050	80	77.8	-	3500K	40°	E26	5.3	4.8	5	12
LED14P38D35KNFL	LED 13.5W P38 DIM 35KNFL	13.5	1050	80	77.8	-	3500K	25°	E26	5.3	4.8	5	12
LED14P38D35KSP	LED 13.5W P38 DIM 35KFL BLAC	13.5	1050	80	77.8	-	3500K	40°	E26	5.3	4.8	5	12
LED14P38D41KFL	LED 13.5W P38 DIM 41KFL	13.5	1050	80	77.8	2678	4100K	40°	E26	5.3	4.8	5	12
LED14P38D41KFLB	LED 13.5W P38 DIM 41KFL BLACK	13.5	1050	80	77.8	2678	4100K	40°	E26	5.3	4.8	5	12
LED14P38D41KNFL	LED 13.5W P38 DIM 41KNFL	13.5	1050	80	77.8	8310	4100K	25°	E26	5.3	4.8	5	12
LED14P38D41KSP	LED 13.5W P38 DIM 41KSP	13.5	1050	80	77.8	13535	4100K	15°	E26	5.3	4.8	5	12
LED14P38D41KSPB	LED 13.5W P38 DIM 41KSP BLACK	13.5	1050	80	77.8	13535	4100K	15°	E26	5.3	4.8	5	12
LED14P38D50KFL	LED 13.5W P38 DIM 50KFL	13.5	1050	80	77.8	2647	5000K	40°	E26	5.3	4.8	5	12
LED14P38D50KFLB	LED 13.5W P38 DIM 50KFL BLACK	13.5	1050	80	77.8	2647	5000K	40°	E26	5.3	4.8	5	12
LED14P38D50KNFL	LED 13.5W P38 DIM 50KNFL	13.5	1050	80	77.8	8071	5000K	25°	E26	5.3	4.8	5	12
LED14P38D50KSP	LED 13.5W P38 DIM 50KNSP	13.5	1050	80	77.8	12418	5000K	15°	E26	5.3	4.8	5	12
<b>LED 15W PAR38 Lamps – 120W Equiv. • Dimmable • 25,000 Hours</b>													
LED17P38D24KFL	LED 15W P38 DIM 24KFL	15	1050	80	70.0	-	2400K	40°	E26	5.3	4.8	5	12
LED17P38D24KNFL	LED 15W P38 DIM 24KNFL	15	1050	80	70.0	-	2400K	25°	E26	5.3	4.8	5	12
LED17P38D24KSP	LED 15W P38 DIM 24KSP	15	1200	80	70.0	-	2400K	15°	E26	5.3	4.8	5	12
LED17P38D27KFL	LED 15W P38 DIM 27KFL	15	1200	80	80.0	2757	2700K	40°	E26	5.3	4.8	5	12
LED17P38D27KFLB	LED 15W P38 DIM 27KFL BLACK	15	1200	80	80.0	2757	2700K	40°	E26	5.3	4.8	5	12
LED17P38D27KNFL	LED 15W P38 DIM 27KNFL	15	1200	80	80.0	8857	2700K	25°	E26	5.3	4.8	5	12
LED17P38D27KSP	LED 15W P38 DIM 27KSP	15	1200	80	80.0	16239	2700K	15°	E26	5.3	4.8	5	12
LED17P38D30KFL	LED 15W P38 DIM 30KFL	15	1200	80	80.0	3106	3000K	40°	E26	5.3	4.8	5	12
LED17P38D30KFLB	LED 15W P38 DIM 30KFL BLACK	15	1200	80	80.0	3106	3000K	40°	E26	5.3	4.8	5	12
LED17P38D30KNFL	LED 15W P38 DIM 30KNFL	15	1200	80	80.0	9274	3000K	25°	E26	5.3	4.8	5	12
LED17P38D30KNFLB	LED 15W P38 DIM 30KNFL BLACK	15	1200	80	80.0	9274	3000K	25°	E26	5.3	4.8	5	12
LED17P38D30KSP	LED 15W P38 DIM 30KSP	15	1200	80	80.0	18492	3000K	15°	E26	5.3	4.8	5	12
LED17P38D30KSPB	LED 15W P38 DIM 30KSP BLACK	15	1200	80	80.0	18492	3000K	15°	E26	5.3	4.8	5	12
LED17P38D30KWFLB	LED 15W P38 DIM 30KWFL BLACK	15	1200	80	80.0	-	3000K	60°	E26	5.3	4.8	5	12
LED17P38D35KFL	LED 15W P38 DIM 35KFL	15	1200	80	80.0	-	3500K	40°	E26	5.3	4.8	5	12
LED17P38D35KFLB	LED 15W P38 DIM 35KFL BLACK	15	1200	80	80.0	-	3500K	40°	E26	5.3	4.8	5	12
LED17P38D35KNFL	LED 15W P38 DIM 35KNFL	15	1200	80	80.0	-	3500K	25°	E26	5.3	4.8	5	12
LED17P38D35KNFLB	LED 15W P38 DIM 35KNFL BLACK	15	1200	80	80.0	-	3500K	25°	E26	5.3	4.8	5	12

## Specifications

ITEM #	DESCRIPTION	WATTS	LUMENS	CRI	LPW	MEASURED CBCP	COLOR TEMP	BEAM ANGLE	BASE	MOL (IN.)	DIA (IN.)	WARRANTY YEARS	# IN CASE
<b>LED 15W PAR38 Lamps – 120W Equiv. • Dimmable • 25,000 Hours</b>												<i>continued....</i>	
LED17P38D35KSP	LED 15W P38 DIM 35KSP	15	1200	80	80.0	-	3500K	15°	E26	5.3	4.8	5	12
LED17P38D41KFL	LED 15W P38 DIM 41KFL	15	1200	80	80.0	2870	4100K	40°	E26	5.3	4.8	5	12
LED17P38D41KFLB	LED 15W P38 DIM 41KFL BLACK	15	1200	80	80.0	2870	4100K	40°	E26	5.3	4.8	5	12
LED17P38D41KNFL	LED 15W P38 DIM 41KNFL	15	1200	80	80.0	9288	4100K	25°	E26	5.3	4.8	5	12
LED17P38D41KNFLB	LED 15W P38 DIM 41KNFLB	15	1200	80	80.0	9288	4100K	25°	E26	5.3	4.8	5	12
LED17P38D41KSP	LED 15W P38 DIM 41KSP	15	1200	80	80.0	18408	4100K	15°	E26	5.3	4.8	5	12
LED17P38D41KSPB	LED 15W P38 DIM 41KSP BLACK	15	1200	80	80.0	18408	4100K	15°	E26	5.3	4.8	5	12
LED17P38D50KFL	LED 15W P38 DIM 50KFL	15	1200	80	80.0	2713	5000K	40°	E26	5.3	4.8	5	12
LED17P38D50KFLB	LED 15W P38 DIM 50KFL BLACK	15	1200	80	80.0	2713	5000K	40°	E26	5.3	4.8	5	12
LED17P38D50KNFL	LED 15W P38 DIM 50KNFL	15	1200	80	80.0	9387	5000K	25°	E26	5.3	4.8	5	12
LED17P38D50KSP	LED 15W P38 DIM 50KSP	15	1200	80	80.0	19721	5000K	15°	E26	5.3	4.8	5	12
<b>LED 18.5W PAR38 High Output Lamps – 150W Equiv. • Dimmable • 25,000 Hours</b>													
LED17HOP38D27KFL	LED 18.5W HOP38 DIM 27KFL	18.5	1500	80	81.1	4346	2700K	40°	E26	5.3	4.8	5	12
LED17HOP38D27KNFL	LED 18.5W HOP38 DIM 27KNFL	18.5	1500	80	81.1	9299	2700K	25°	E26	5.3	4.8	5	12
LED17HOP38D27KSP	LED 18.5W HOP38 DIM 27KSP	18.5	1500	80	81.1	21535	2700K	15°	E26	5.3	4.8	5	12
LED17HOP38D30KFL	LED 18.5W HOP38 DIM 30KFL	18.5	1500	80	81.1	4365	3000K	40°	E26	5.3	4.8	5	12
LED17HOP38D30KFLB	LED 18.5W HOP38 DIM 30KFL BLACK	18.5	1500	80	81.1	4365	3000K	40°	E26	5.3	4.8	5	12
LED17HOP38D30KNFL	LED 18.5W HOP38 DIM 30KNFL	18.5	1500	80	81.1	12782	3000K	25°	E26	5.3	4.8	5	12
LED17HOP38D30KNFLB	LED 18.5W HOP38 DIM 30KNFL BLACK	18.5	1500	80	81.1	12782	3000K	25°	E26	5.3	4.8	5	12
LED17HOP38D30KSP	LED 18.5W HOP38 DIM 30KSP	18.5	1500	80	81.1	23699	3000K	15°	E26	5.3	4.8	5	12
LED17HOP38D30KSPB	LED 18.5W HOP38 DIM 30KSP BLACK	18.5	1500	80	81.1	23699	3000K	15°	E26	5.3	4.8	5	12
LED17HOP38D35KFL	LED 18.5W HOP38 DIM 35KFL	18.5	1500	80	81.1	-	3500K	40°	E26	5.3	4.8	5	12
LED17HOP38D35KFLB	LED 18.5W HOP38 DIM 35KFL BLACK	18.5	1500	80	81.1	-	3500K	40°	E26	5.3	4.8	5	12
LED17HOP38D35KNFL	LED 18.5W HOP38 DIM 35KNFL	18.5	1500	80	81.1	-	3500K	25°	E26	5.3	4.8	5	12
LED17HOP38D35KSP	LED 18.5W HOP38 DIM 35KSP	18.5	1500	80	81.1	-	3500K	15°	E26	5.3	4.8	5	12
LED17HOP38D35KWFL	LED 18.5W HOP38 DIM 35KWFL	18.5	1500	80	81.1	-	3500K	60°	E26	5.3	4.8	5	12
LED17HOP38D41KFL	LED 18.5W HOP38 DIM 41KFL	18.5	1500	80	81.1	4604	4100K	40°	E26	5.3	4.8	5	12
LED17HOP38D41KNFL	LED 18.5W HOP38 DIM 41KNFL	18.5	1500	80	81.1	11614	4100K	25°	E26	5.3	4.8	5	12
LED17HOP38D41KSP	LED 18.5W HOP38 DIM 41KSP	18.5	1500	80	81.1	22458	4100K	15°	E26	5.3	4.8	5	12
LED17HOP38D50KFL	LED 18.5W HOP38 DIM 50KFL	18.5	1500	80	81.1	4446	5000K	40°	E26	5.3	4.8	5	12
LED17HOP38D50KNFL	LED 18.5W HOP38 DIM 50KNFL	18.5	1500	80	81.1	12467	5000K	25°	E26	5.3	4.8	5	12
LED17HOP38D50KSP	LED 18.5W HOP38 DIM 50KSP	18.5	1500	80	81.1	21535	5000K	15°	E26	5.3	4.8	5	12

SUGGESTED DIMMER COMPATIBILITY	
MANUFACTURER	MODEL NUMBER
Leviton	R50-IPLO6-10M
	R61-06674-POI
Lutron	CTCL-153PDH-WH
	TGCL-153PH-WH
	DVVCL-153PH-WH

Note: E26 compatible dimmer

For the most up-to-date specs, please visit [www.tcp.com](http://www.tcp.com)



PAR20



PAR30SN



PAR30



PAR38



For the most up-to-date specs, please visit [www.tpci.com](http://www.tpci.com)



# TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 30 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit [tcp.com](http://tcp.com)

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516